

TeleProffs GO

BRANDVÄGGSREGLER

SNABBGUIDE 4.0

Mina sidor

Samtliga användare i TeleProffs GO har tillgång till en personlig webbsida. Här kan du bland annat administrera ditt mobilabonnemang (gäller endast TeleProffs GO-abonnemang), hämta hem och konfigurera mobilapp/softphone, samt hantera din användare och telefonnummer.

Mina Sidor nås via <https://minasidor.teleproffs.se> och du loggar in med ditt fastnät nummer i +46-format (ex +4636305525)



Firewall Settings

Notes to observe:

- * The table below shows the traffic going between the customer's network and TeleProffs GO
- * Note that all SIP-inspection or SIP ALG-functionality must be turned off in the firewall
- * Media/Speech is negotiated dynamically in the SDP for every call. Therefore it is necessary to allow the whole port span.

To	Destination port	Protocol	Transport	Rule	Comments
Teleproffs GO					
185.39.124.0/22	80 / 443	HTTP(S)	TCP	Allow	
212.247.59.0/27	80 / 443	HTTP(S)	TCP	Allow	
185.39.124.0/22	5060 / 5061	SIP	TCP / UDP	Allow	
212.247.59.0/27	5060 / 5061	SIP	TCP / UDP	Allow	
185.39.124.0/22	10000-65534	RTP / SRTP	UDP	Allow	
212.247.59.0/27	10000-65534	RTP / SRTP	UDP	Allow	

Below displays optional firewall settings if you are using desk phones from Mitel or Snom.

To	Destination port	Protocol	Transport	Rule	Comments
Mitel Phone					
1.aastra.pool.ntp.org	123	NTP	UDP	Allow	Used for date/time in fixed phones
2.aastra.pool.ntp.org	123	NTP	UDP	Allow	Used for date/time in fixed phones
3.aastra.pool.ntp.org	123	NTP	UDP	Allow	Used for date/time in fixed phones
0.se.pool.ntp.org	123	NTP	UDP	Allow	Used for date/time in fixed phones
rca.aastra.com	80 / 443	HTTP(S)	TCP	Allow	Mitel phone settings distribution
SNOM Phone					
185.39.124.0/22	9443	HTTPS	TCP	Allow	Used for provisioning of Snom phones
212.247.59.0/27	9443	HTTPS	TCP	Allow	Used for provisioning of Snom phones
52.28.89.237	443	HTTP(S)	TCP	Allow	Snom phone setting distribution

TeleProffs always strongly recommend that the customer uses equipment designed for business-use.